


CORRY **Micronics** **PRODUCT SPECIFICATION**

GF0125-01-001

GLASS SEALED DC FEEDTHRU



(X.XX) = MILLIMETERS

Materials:

Case: Kovar

Lead: Kovar

Finish: Gold Plating per Mil-G-45204C, Type III, Class 0

Glass: Corning 7052 or Equivalent

Insulation Resistance: 10 GΩ Min.

Working Voltage: 200 VDC

Dielectric Withstanding Voltage: 500 VDC

Maximum Current: 10 Amps

Operating Temperature: -55°C +125°C

Hermeticity: < 1 x 10⁻⁸ CC / Sec. Per Mil-Std-202

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(814) 664-7728 Fax (814) 664-4582 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with it's intended use. CMI also reserves the right to change this document without notice.