



HS72-XX-XXXX HERMETICALLY SEALED FILTERS 100 VDC RATED



Case: Tin/lead Plated, Hermetically Sealed.
I.R. @ 25 °C: 1000Ω-F Min.
Rated Voltage: 100 vdc
Capacitance: 1.4uF @ 1kHz, 25°C
Operating Temperature: -55 °C - +125 °C



PART NUMBER	I (Amps)	Crkt	DCR (Ohms)	"T"	TYPICAL NO LOAD INSERTION LOSS (dB) @ 25 °C PER MIL-STD-220						
					30 kHz	150 kHz	300 kHz	1 MHz	10 MHz	100 MHz	1 GHz
HS72-21-1001	.5A	LB	.3	.312	20	43	55	70	70	70	70
HS73-21-1001	.5A	LT	.3	.312	20	43	55	70	70	70	70
HS72-21-1101	1.0A	LB	.21	.312	16	40	52	70	70	70	70
HS73-21-1101	1.0A	LT	.21	.312	16	40	52	70	70	70	70
HS72-21-1501	5.0A	LB	.01	.312	16	29	34	47	70	70	70
HS73-21-1501	5.0A	LT	.01	.312	16	29	34	47	70	70	70
HS72-21-1601	10.0A	LB	.005	.312	16	24	34	44	70	70	70
HS73-21-1601	10.0A	LT	.005	.312	16	24	34	44	70	70	70

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

**Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(814) 664-7728 Fax (814) 664-4582 www.cormic.com**

Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with it's intended use. CMI also reserves the right to change this document without notice.