


**CMIBPF-29G-45M**  
**Band Pass Filter**

Frequency Range	29.196 – 29.241 GHz
Insertion Loss	2.5 dB
VSWR	1.5
Ripple In Band	±0.35 dB
Group Delay (peak to peak)	1 ns
Rejection: DC - 28 GHz	80 dB
Rejection: 28 - 29 GHz	40 dB
Rejection: 29.5 - 30 GHz	40 dB
Rejection: 30 - 40.4 GHz	80 dB
Operating Temperature	-30° - +70° C
Impedance	50Ω
Connectors	2.92 Female / 2.92 Male
Finish	Black Paint



**CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.**

**Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407**  
**(724) 940-7556 ext. 138 Fax (724) 940-7707 [www.cormic.com](http://www.cormic.com)**

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with it's intended use. CMI also reserves the right to change this document without notice. 3/20/17