


CMIDBPF-880-915M DIELECTRIC BAND PASS FILTER

Parameter	Specification
Pass Band Frequency	880 to 915MHz
Pass Band Insertion Loss	4 dB max
Ripple in Pass Band	± 1.25 dB
VSWR	1.5:1
Rejection at 925MHz	-40 dB min
Impedance	50 Ω
Connectors	SMA-F (2)
Operating Temperature	-40° C to +85° C
Storage Temperature	-55° C to +95° C
Size	See attached Drawing



1. Dimensions are in mm [Inches]
2. Tolerances: Outline drawing: ±0.3 [0.011]
Hole: ±0.2 [0.008]

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with it's intended use. CMI also reserves the right to change this document without notice. 04/13/2016