




CORRY MICRONICS, INC PRODUCT SPECIFICATION

CMISFB-80180T4 Switch Filter Bank

Electrical Specifications	
Parameter	Specification
Frequency Range	8 – 10 GHz 10 – 12 GHz 12 – 15 GHz 15 – 18 GHz
Insertion Loss	8 dB Max
Band Flatness	± 1.5 dB Max
Out of Band Rejection	40 dB at FL – 1.5 GHz; FH + 1.5 GHz Min
VSWR	2.0:1 Max
Switching Speed	100 nS Max
Isolation	60 dB Min
Power Supply	+5V / 100mA
Port Connectors	SMA Female
Operating Temperature	-20° C ~ +70° C
Surface Finish	Natural Color Conductive Oxidation



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with it's intended use. CMI also reserves the right to change this document without notice. 08/22/2017