


CMILNA-08120F45 8-12 GHz LOW NOISE AMPLIFIER

Electrical Specifications

| Parameters | Specifications | |
|-----------------|------------------------------------|--|
| Frequency Range | 8~12GHz | |
| Gain | ≥25dB | |
| Gain Flatness | ≤±1.5dB | |
| Noise Figure | ≤4.5dB | |
| VSWR | ≤2.5:1 | |
| P1dB | ≥8dBm | |
| Power Supply | +15V/120mA | |
| Port Connectors | SMA-Female | |
| Operating Temp. | -20°C~+70°C | |
| Surface Finish | Natural color conductive oxidation | |

Dimensions (Inches)



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407 (724) 940-7556 ext. 138 Fax (724) 940-7707 *www.cormic.com*

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with it's intended use. CMI also reserves the right to change this document without notice. 03/08/2017