

## CMISP10A-4080P05 4 – 8 GHz Single Pole Ten Throw Absorptive Switch

Electrical Specifications								
Parameter	Specification							
Frequency Range	4 ~ 8 GHz							
Insertion Loss	≤2.5 dB							
VSWR	≤1.5:1							
Isolation	≥50 dB							
Max Input Power	+27 dBm CW							
Switching Speed	≤50 ns (50% TTL to 10%/90% RF)							
Power Supply	+5 V (300 mA), -5 V (-50 mA)							
Input/Output Connector	SMA Female							
Control Level	TTL							
Surface Finish	Natural Color Conductive Oxidation							
Operating Temperature	-40° C ~ +70° C							
Dimensions	See Attached Drawing (Dimensions are in mm)							

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407 (724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com




## CORRY MICRONICS, INC PRODUCT SPECIFICATION

## Truth Table:

E1	E2	E3	E4	E5	E6	E7	E8	E9	E10	J1	J2	J3	J4	J5	J6	J7	J8	J9	J10
0	1	1	1	1	1	1	1	1	1	ON	OFF								
1	0	1	1	1	1	1	1	1	1	OFF	ON	OFF							
1	1	0	1	1	1	1	1	1	1	OFF	OFF	ON	OFF						
1	1	1	0	1	1	1	1	1	1	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF
1	1	1	1	0	1	1	1	1	1	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF
1	1	1	1	1	0	1	1	1	1	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF
1	1	1	1	1	1	0	1	1	1	OFF	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF
1	1	1	1	1	1	1	0	1	1	OFF	ON	OFF	OFF						
1	1	1	1	1	1	1	1	0	1	OFF	ON	OFF							
1	1	1	1	1	1	1	1	1	0	OFF	ON								

## Outline Drawing:

All Dimensions in mm



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407