


RF FILTER SPECIFICATION

Part No. BP65R881S30A(5DR35-881.5/H30)


| Electrical Specifications | | | |
|---------------------------|------------------------------|--------------------|----------|
| Item | Parameter | CMI Specification | Unit |
| 1 | Center Frequency [fo] | 881.5 | MHz |
| 2 | Bandwidth (0.5dB BW) | 30 min. | MHz |
| 3 | Insertion Loss at fo | 2.1 max. | dB |
| 4 | V S W R at fo | 1.5 | |
| 5 | In/Out Impedance | 50 | Ω |
| 6 | Attenuation [Relative value] | 15 min. at 849 MHz | dBc |
| 7 | Temperature Range | -20°C ~ +85°C | °C |

TOP VIEW



TOLERANCE : .X ± 0.3
 .XX ± 0.15
 DIMENSION UNIT : mm
 ● : INPUT PORT
 ▨ : SOLDER MASK
 ▩ : GOLD PLATING

BOTTOM VIEW



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(814) 664-7728 Fax (814) 664-4582 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with it's intended use. CMI also reserves the right to change this document without notice.