

Product Specification

CMIVCPS08001800A Voltage Control Phase Shifter 4 - 8 GHz

Electrical Specifications

Parameter	Specification
Frequency Range	8 ~ 18 GHz
Phase Range	360° Typ.
Insertion Loss	6.0 dB Typ. 8.0 dB MAX
Insertion Loss Temperature Coefficient	0.003 dB/ °C Typ.
Phase Flatness	±15° Typ.
Control Voltage	0.0 V MIN 13.0 V Typ.
Input Return Loss (0V)	6 dB MIN 8 dB Typ.
Output Return Loss (0V)	6 dB MIN 8 dB Typ.
0.1 dB Compression Point (P0.1dB)	23 dBm Typ.
Current	5 mA
Impedance	50 Ω
Weight	0.5 Ounces
Input / Output Connectors	SMA-Female
Finish	Gold Plated
Material	Aluminum
Altitude	30,000 ft. (Epoxy Sealed Controlled Environment)
	60,000 ft 1.0 psi min (Hermetically Sealed Un-Controlled Environment) (Optional)
Vibration	25 gRMS [15 degrees 2 kHz] endurance, 1 hr/axis
Humidity	100% RH @ 35° C, 95% RH @ 40° C
Shock	20 G for 11 msec Half Sine Wave, 3 Axis Both Directions
Dimensions	See Attached Drawing (Dimensions are in mm)

Absolute Maximum Ratings

Control Voltage	0 ~ +15V
RF Input Power	+26 dBm

Outline Drawing

