

Product Specification

CMIPA-G09P32 935-960 MHz GSM SOLID STATE HIGH POWER AMPLIFIER

Electrical Specifications

Parameters	Specifications	Note
Operating Frequency	935-960MHz	
Signal Type	GSM, PAR 0dB	
Nominal Output Power	32W	
Nominal Gain	33dB	
Gain with ALC off +/- 1 dB	33 ± 1dB	Room temperature Value of attenuator 8.5dB
	33 ± 1.5dB	Low and high temperature Value of attenuator 8.5dB
Input return loss	18dB	
Output return loss	18dB	
Tx ALC control range vs. Tx input level change, Min.	16 dB (Nominal input +/-8dB)	
ALC set range	16dB (45dBm~30dBm)	
ALC set step	0.5dB	
ALC Control Accuracy	± 1 dB	
Attenuator Set Range	31dB	ALC OFF
Attenuator Set Step	0.25dB	ALC OFF
Initial value of attenuator	8.5dB	
Max input level, no damage and degradation	+15dBm	Adjust the attenuator to maintain output power
Noise Figure	≤20dB	ALC OFF
DC Power	+28V	
Efficiency	≥40%@32W	
Output load mismatch tolerance	Isolator protected	

Electrical Specifications [Cont'd]

Parameters	Specifications	Note
Max operating base temperature	90°C	If temp higher than 90°C, the PA will be shut down
Power consumption when muted	<5W	
Forward power monitor	Range: 30dB, 48dBm~19dBm Resolution: 0.1dBm Accuracy: ± 2 dB	
Reverse power monitor	Range: 30dB, 48dBm~19dBm Resolution: 0.1dBm Accuracy: ± 2 dB	
DC Current monitor	Range: 0-15A Resolution: 0.1A Accuracy: $\pm 5\%$	
Temperature monitor	Range: -40°C~+105°C Resolution: 1°C Accuracy: ± 3 °C	

Environmental Specifications

- Environment Temp.: 0°C ~ +50°C
- Humidity: 5%RH~96%RH
- Atmospheric Pressure: 70kPa~106kPa

Dimensions (Inches)

